

Vertical Intake Centrifugal Type Air Curtain (Plastic Type)

上吸风型离心式风幕机 (塑料型)



Ambient without heating 普通风

The integrated plastic casing gives a more streamlined appearance and stronger corrosion resistance performance. 全塑料一体化成型机壳, 令外形更体现流线型设计和防腐性能提高。

Quality motor runs for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。

Multiple unit specifications: 900mm, 1200mm, 1500mm. 多种机身长度规格: 900mm, 1200mm, 1500mm。

Various installation heights available: 3.0m, 3.5m, 4.0m, 4.5m. 适用安装高度: 3.0m, 3.5m, 4.0m, 4.5m。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Installation Height (m)	功率 Power(W)			风速 Air Speed(m/s)			风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)
				低档 Low	中档 Medium	高档 High	低档 Low	中档 Medium	高档 High				
FM3509L-2 FM3509L-Y-2	900	220V~/50Hz/1Ph	3.0~3.5	175	217	295	10.0	12.5	15.0	1020	53	900 × 231.5 × 216	12.0
FM3512L-2 FM3512L-Y-2	1200			235	272	360				1360	54	1200 × 231.5 × 216	16.0
FM3515L-2 FM3515L-Y-2	1500			272	333	455				1700	56	1500 × 231.5 × 216	20.6
FM4509L-2 FM4509L-Y-2	900		4.0~4.5	15.0	345	375	475	17.5	20.0	1425	64	900 × 231.5 × 216	12.0
FM4512L-2 FM4512L-Y-2	1200				430	490	625			1900	65	1200 × 231.5 × 216	16.0
FM4515L-2 FM4515L-Y-2	1500				600	655	820			2375	66	1500 × 231.5 × 216	20.6

Remark: Customized rated voltage and frequency are available.
There are only High / Low air speed settings for the common type.

备注: 可根据客户的额定电压和频率来订做合适的产品。
普通型产品仅有高、低两档调速。

Vertical Intake Centrifugal Type Air Curtain

上吸风型离心式风幕机



Ambient without heating 普通风

Metal casing, strong fire resistance, easy installation. 全金属外壳, 防火性能高, 安装方便。

Quality motor runs for 5000 hours continuously without any defects. 电机持续运行超过5000小时无故障。

Multiple unit specifications: 600mm, 900mm, 1000mm, 1200mm, 1500mm & 1800mm. 多种机身长度规格: 600mm, 900mm, 1000mm, 1200mm, 1500mm & 1800mm。

Various installation heights available: 3.0m, 3.5m, 4.0m, 4.5m. 适用安装高度: 3.0m, 3.5m, 4.0m, 4.5m。

Electrical Ratings 技术参数

产品型号 Model No.	规格 Specification (mm)	额定电压/频率/相数 Voltage/Frequency/Phase	安装高度 Installation Height (m)	功率 Power(W)			风速 Air Speed(m/s)			风量 Air Volume (m ³ /h)	噪音 Noise (dB)	外型尺寸 Unit Size (mm)	净重 Net Weight (kg)				
				低档 Low	中档 Medium	高档 High	低档 Low	中档 Medium	高档 High								
FM3506D FM3506DY	600	220V~/50Hz/1Ph	3.0~3.5	115	145	186	10.0	12.5	15.0	680	52	600 × 230 × 212	9.9				
FM3509D FM3509DY	900			186	238	322				1020	53	900 × 230 × 212	14.8				
FM3510D FM3510DY	1000			186	238	322				1020	53	1000 × 230 × 212	15.1				
FM3512D FM3512DY	1200			218	285	419				1360	54	1200 × 230 × 212	18.7				
FM3515D FM3515DY	1500			291	381	536				1700	56	1500 × 230 × 212	23.6				
FM3518D FM3518DY	1800			314	420	628				2040	57	1800 × 230 × 212	27.8				
FM4506D FM4506DY	600			4.0~4.5	15.0	230				265	285	17.5	20.0	950	63	600 × 230 × 212	9.9
FM4509D FM4509DY	900					342				366	417			1425	64	900 × 230 × 212	14.8
FM4510D FM4510DY	1000					342				366	417			1425	64	1000 × 230 × 212	15.1
FM4512D FM4512DY	1200					450				476	539			1900	65	1200 × 230 × 212	18.7
FM4515D FM4515DY	1500					639				700	731			2375	68	1500 × 230 × 212	23.6
FM4518D FM4518DY	1800					633				690	793			2850	68	1800 × 230 × 212	27.8

Remark: Customized rated voltage and frequency are available.
There are only High / Low air speed settings for the common type.

备注: 可根据客户的额定电压和频率来订做合适的产品。
普通型产品仅有高、低两档调速。